

PGJ12.MH47907 Printing Materials - Component

Page Bottom

Printing Materials - Component

[See General Information for Printing Materials - Component](#)

TOOTECH

MH47907

309HO ENC VENTURE DREAM TOWER 6TH
197-28 GURO-DONG GURO-GU
SEOUL, 152-719 REPUBLIC OF KOREA

Label materials suitable for additional printing using one or more of the following inks.

Inks

1 - ITW "B324", Ricoh "B110CR", Armor " AXR7+" thermal transfer ribbons.


2 - TOOTECH "TTE-7" (Dark Gray) series Laser engraving machines

Pressure-sensitive systems:

Model Dsg.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Unprinted stock dsg: LSG01-NN Inks: 2						
	Acrylic paint (AC PT)	125	-40	X	X	-
	Aluminum (AL)	125	-40	X	X	-
	Galvanized steel (GS)	125	-40	X	X	-
	Porcelain (PRCLN)	125	-40	X	X	-
	Stainless steel (SS)	125	-40	X	X	-
	Alkyd paint (AK PT)	100	-40	X	X	-
	Melamine (ME)	100	-40	X	X	-
	Polyester paint (PER PT)	100	-40	X	X	-
	Polyester powder paint (PER PDR PT)	100	-40	X	X	-
	Polyvinyl fluorine (PVF)	100	-40	X	X	-
	Unsaturated polyester - thermoset (UP)	100	-40	X	X	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	X	-
	Polycarbonate (PC)	80	-40	X	X	-
	Polystyrene (PS)	80	-40	X	X	-
Unprinted stock dsg: LSG01-OL Printed label dsg: LSG01-OP Inks: 1, 2						
	Acrylic paint (AC PT)	125	-40	X	X	-
	Aluminum (AL)	125	-40	X	X	-
	Galvanized steel (GS)	125	-40	X	X	-
	Porcelain (PRCLN)	125	-40	X	X	-
	Stainless steel (SS)	125	-40	X	X	-
	Alkyd paint (AK PT)	100	-40	X	X	-
	Melamine (ME)	100	-40	X	X	-
	Polyester paint (PER PT)	100	-40	X	X	-

Polyester powder paint (PER PDR PT)	100	-40	X	X	-
Polyvinyl Fluoride (PVF)	100	-40	X	X	-
Unsaturated polyester - thermoset (UP)	100	-40	X	X	-
Acrylonitrile butadiene styrene (ABS)	80	-40	X	X	-
Polycarbonate (PC)	80	-40	X	X	-
Polystyrene (PS)	80	-40	X	X	-

Note: Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Marking: Company name, model designation and Recognized Component Mark,  .
Last Updated on 2010-11-09

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright ?2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

